

SS3520 SLIMFRONT WINDOW WALL

- Glass
 - %6" Laminated
 - 13/16" Laminated insulating
 - High-performance low-E and tints
- Design pressures
 - Up to +90/-120, provide security, safety, and performance in wind-borne debris areas

- Narrow sight lines
 - 1" x 5" System with slim sight lines
- Robust sizes
 - Up to 15' high
- External wet glaze
 - Creates an exterior barrier
- Inside Glazed

- Glazing
 - Fully captured on all four sides, 2-part silicone DOW 983
 - White, Bronze, or Clear Anodized finish options
 - Optional mill finish and custom colors
- No Jamb Anchor required

PANEL SIZE	GLASS	FRAME TYPE	DP RATING
48" x 90 ¾"	%16" HS PVB or 11/4" LIG	5" Unreinforced	+70/-80 psf
48" x 120"	%16" HS SG or 11/4" LIG	5" Steel Reinforced	+90/-120 psf
60" x 120"	%16" HS SG or 11/4" LIG	5" Steel Reinforced	+90/-100 psf
48" x 144"	%16" HS SG or 11/4" LIG	5" Steel Reinforced	+61.5/-68.3 psf
60" x 144"	%16" HS SG or 11/4" LIG	7" HD Unreinforced	+60/-60 psf
48" x 180"	%6" HS SG or 11/4" LIG	7" HD Steel Reinforced	+60/-60 psf

	WIDTH	HEIGHT
MINIMUM SIZES		
Storefront panel system	14 1/2"	14 ½"
MAXIMUM SIZES		
Storefront panel system unreinforced	48"	97¾"
Storefront panel system steel reinforced	60" 48"	120" 144"
Storefront HD panel system unreinforced	60"	144"
Storefront HD panel system reinforced	48"	180"

[Refer to certification document for performance requirements and options]

OTHER STANDARD FEATURES

- 6063-T6 aluminum alloy
- 1"x5" frame member
- 1"x7" HD frame member
- HD panel system unreinforced
- Stainless-steel assembly screws
- FBC Certification

OPTIONS

- Custom frame colors
- White interlayer
- Clear/various tint options
- Low-E coatings
- · Argon Gas